

TRAMIGO

TRACKING & CONNECTIVITY



COMPLETE SOLUTION

TRAMIGO TF150

VERSATILE & AFFORDABLE
TRACKING FOR ALL VEHICLES

Tramigo TF150 is an affordable and versatile GPS tracking solution designed for a wide range of vehicles, from motorbikes to heavy-duty trucks. Powered by Tramigo's firmware, it ensures reliable performance and receives over-the-air updates for the latest features and improvements. With full access to Tramigo's software and multi-network connectivity, the TF150 offers advanced features like geofencing, real-time alerts, and remote vehicle immobilization, providing enhanced security and control for fleet of all sizes.



TRAMIGO TF150 FEATURES



**PRECISE LIVE
TRACKING**



**GEO-FENCE
ALARMS**



**SUPPORTS
9-90V**



**IGNITION
DETECTION
ALARMS**



**MOTION
DETECTION
ALARMS**



**REMOTE
IMMOBILIZATION**



**BUILT-IN
eSIM**



**MULTI-NETWORK
CONNECTIVITY**



**BUILT-IN
BATTERY**

TRAMIGO SOFTWARE

Tramigo offers software solutions which allows you to monitor your vehicles at your control center or from your mobile devices:

• TRAMIGO CLOUD

TramigoCloud allows you to track your fleet behind a secure web login and puts a full control center within your reach wherever you go. With centralised updates the latest features are always immediately available to all of our security focused customers. TramigoCloud is recommended for fleet management.



• TRAMIGO APP

TramigoApp is an easy but secure way to track and monitor your vehicles anytime and anywhere. TramigoApp allows you to monitor and track your vehicles, staff, or family directly on your phone. Additional features includes trip reports, usage history reporting, geofence and setting alarms. Available for free on App Store and Google Play.



TRAMIGO APP



TRAMIGO CLOUD



TRACK ANYWHERE ANYTIME

TRAMIGO TF150 TECHNICAL DATA

Dimension	78(L) x 40(W) x 15(H) mm
Network Standards	GSM/GPRS (850/900/1800/1900 MHz)
GNSS Support	GPS, GLONASS, Galileo, Beidou, QZSS, SBAS
Channels	56 search channels and 16 acquisition channels
Low Power Modes	Sleep, Stop, and Standby modes
Operating Temperature	-40°C to +85°C

Voltage	9-90VDC
Time To Fix (open sky)	Hot start 1s Cold start 35s
Backup Battery	200mAh
G-sensor	3-Axis Digital Accelerometer up to $\pm 8G$
Power Consumption	Active mode: ~ 36 mA (at 72 MHz) Sleep mode: ~ 20 μA (with peripherals disabled) Standby mode: ~ 2 μA